



**Optic  
Clear  
Solutions**

**KleArmor™  
Lunar White  
Transparent Acrylic  
Filter**

**Catalog Listing**  
91578GU-LLWWXXX-  
YTIw-Cx-U

**Drawn by:** RPH

**Revision:** A    **Date:** 30AUG21

**Scale:** None

**Tolerances:** See Figure

**Approval:** Sam Truong

**Sheet 1 of 1**

Optic Clear Solutions LLC, California

**Notes: Unless Otherwise Specified.**

1. Material: UV stabilized, colored, polymethylmethacrylate sheet per ASTM-D4802, Category 1A, preshrunk and annealed per MIL-P-5425. Molecular Cross Linked 2%.
2. Standard Finish: When specified, material is finished with specular or non-specular surfaces.
3. Optional Finish: A/R or hard coating available for improved glare management and surface durability.
4. Available cross section: .020 inches to 1.0 inches.
5. Available sheet sizes: Up to 24 inches by 36 inches.
6. Sheets are provided with protective masking.
7. Optical Specifications:
  - Index of Refraction: 1.48 – 1.50
  - Photopic Transmittance: 68% @ 2854K
  - UV Transmission: 200nm – 400nm 5% max
  - Haze: 3 % max
  - Specular surface, scratch and dig: 60 – 40 max
  - Non-specular gloss when specified: 85 +/- 10 GU
  - Inclusions: 0%